



Models	CRF300L CRF300L
GENERAL	
Warranty	2 yrs or 24000 kms WHICH EVER COMES FIRST (conditions apply)
Service Intervals	3500 km
0 - 100 km/h (sec)	-
DIMENSIONS AND WEIGHTS	
Claimed KERB Weight	142
Length (mm)	2230
Width (mm)	820
Height (mm)	1200
Seat height (mm)	880
Rake/Trail (°/mm)	109
Wheel Base	1455
DRIVE	
Drive	Chain
Front Suspension	43mm telescopic USD fork
Rear Suspension	Prolink
ENGINE	
Tank Capacity (l)	7.8
Starter	Electric
Engine Configuration	Liquid-cooled, single cylinder DOHC
Cylinders	1
Valves per Cylinder	4
Capacity	286
Power (KW)	20.1kW/8500rpm
Torque (NM)	26.6Nm/6,500rpm
Gearbox	6-spd
SAFETY	
Brakes	2 channel ABS (f) 256mm x 3.5mm disc with two piston caliper (r) 220 mm x 4.5mm disc with single piston caliper
STYLING	
Frame Material	Steel semi-double cradle
WHEELS	
Tyres Front	80/100-21M/C 51P
Tyres Rear	120/80-18M/C 62P
Wheels	Aluminium spoke
STANDARD AVAILABLE ACCESSORIES	
Luggage	-
Maintenance	-
Comfort	-
Utility	-

DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, indirect, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.