

Models	XR125L XR125L
GENERAL	ANIZSE
Warranty	2 yrs or 24000 kms WHICH EVER COMES FIRST (conditions apply)
Service Intervals	3500 km
0 - 100 km/h (sec)	-
DIMENSIONS AND WEIGHTS	
Claimed KERB Weight	130
Length (mm)	2100
Width (mm)	810
Height (mm)	1125
Seat height (mm)	825
Rake/Trail (°/mm)	-
Wheel Base	1450
DRIVE	
Drive	Chain
Front Suspension	31mm telescopic fork, 160mm axle travel
Rear Suspension	Single Shock, Single Tube, 150mm axle travel
ENGINE	
Tank Capacity (I)	12
Starter	Electric and Kick
Engine Configuration	Air-cooled 4-stroke 2-valve OHV single
Cylinders	1
Valves per Cylinder	2
Capacity	124.1
Power (KW)	8.5KW / 8,500 RPM
Torque (NM)	10.6 NM / 7,000 RPM
Gearbox	5-spd
SAFETY	
Brakes	(f) 240mm Hydraulic Disk (r) 110mm leading/trailing drum
STYLING	
Frame Material	Semi-Double Cradle; steel
WHEELS	
Tyres Front	90/90-19
Tyres Rear	110/90-17
Wheels	Wire Spoke Wheel
STANDARD AVAILABLE ACCESSORIES	
Luggage	-
Maintenance	-
Comfort	_

DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.